## CURVED DOUBLE ARM WALL LIGHT IN BRASS - US WIRING

R



Code: 4425

## RU EDITIONS

A pair of mouth-blown glass storm shades held in place by two curved arms. The light is made from components of sand-cast and machined brass, the brass left un-lacquered and slightly brushed. Alternative frosted shades available upon request

> Finish: Solid Brass US wiring Bulb required (not included) : E12, 40W max

> > Available Immediately

Dimensions:

H 39cm x W 29cm x D 30cm H 15½" x W 11½" x D 12"

R



## ROSE UNIACKE DOUBLE CURVED WALL LIGHT INSTALLATION INSTRUCTIONS (US)

CAUTION:

It is recommended that this fixture is installed by a qualified electrician. Please read the instructions fully before installing. INSTALLATION INSTRUCTIONS:

INSTALLATION INSTRUCTIONS: I. Unpack all the parts and place them on a clean surface, do not discard the packaging material until the assembly is completed. 2. Mark the hole location on the wall using a pencil with the mounting hole template and a spint level. Drill holes. Servedriver: Screws should portulate slightly from the wall to allow for the back plate to hang. 4. Connect the wires to the mains supply. 4. Connect the wires to the mains supply. 5. Concer the wires to the mains supply. 5. Concer the light is secured to the wall, insert the glass before inserting the bulk, plate. 5. Once the light is secured to the wall, insert the glass before inserting the bulk. Only use the recommended bulk type and waltage as specified on the lamp holder.

nect the wires to the mains supply. Fully mount the wall light on the screws using the keyholes on the back plate. ise the light is secured to the wall, insert the glass before inserting the bulb. Only use commended bulb type and waitage as specified on the lamp holder.



